

# CCD-720p

1.3MP / WDR / Day & Night

Box Network Camera

HD 720P **CCD** Internet Protocols Camera



30 FPS



Low Light



SD Card



True Day/Night

ONVIF

## Features

HD720P @ 30fps

SONY ICX692 1/3" CCD Sensor

Built-in 32G Micro SD Local Record

H.264,M-JPEG Quad Streaming

Local Analog TV Out

ONVIF 2.0

Two Way Audio

Select Area BLC, High WDR



E-mail : [service@multitek.com.tw](mailto:service@multitek.com.tw)

Web : [www.multitek.com.tw](http://www.multitek.com.tw)

# CCD-720p

1.3MP / WDR / Day & Night

## Box Network Camera

### Technical Specifications

System	
SoC	GrainMedia GM8128
Lens Type	Auto DC-IRIS Support ,D-IRIS Driver: Max 50mA
IRIS	DC-IRIS ON / OFF
ICR	Supported
Audio	2 Way Audio (Mic-in x 1,Audio out x 1)
Shutter Time	Auto / Manual 1/30~1/10000
Interface	RS485
Power Supply	12V DC , PoE IEEE802.3af
Network Interface	Ethernet 10/100 Mbps
Video	
Compression	H.264 Up to 30fps at HD 720P / M-JPEG Up to 30fps at HD 720P
Transport Protocol	UDP , TCP , HTTP , Multicast
Image setting	
S/N Ratio	max 52dB
Auto Exposure	1/30~1/10000s
White Balance	Auto / Manual
Gamma	0.45~1
AGC Gain Control	On / Off
WDR	Off , Low , Middle , High
BLC	135Area(15x9)Can be Select
Audio	
Compression	G.711 audio encoding, bitrate:64 kbps, u-Law or A-Law mode selectable G.726 audio encoding, bitrate:64/32kbps
Networking	
Protocols	UDP, TCP, RTP, RTCP, RTSP, HTTP, FTP, DHCP,IGMP, ICMP, ARP, SMTP, Bonjour, SNMP, UPnP,QoS, NTP, DNS, DDNS, PPPoE
Operating Environments	
Temperature	-20°C~50°C(-4°F~122°F)
Humidity	20%~90%



E-mail : [service@multitek.com.tw](mailto:service@multitek.com.tw)  
Web : [www.multitek.com.tw](http://www.multitek.com.tw)