

MNIZ-32P8HR5

Megapixel recording, dual streaming and high-capacity RAID storage

IP surveillance NVR



Hardware Specification

32 CH

Intel® H61 Chipset, LGA 1155 socket for Intel® Sandy/Ivy Bridge Processors

CPU: Core i5

DOM: 1GB, Memory: 4GB (in order to have better performance, suggest 4GB x 1 for 16CH or above)

VGA*1, HDMI*1

Audio input*1, Audio output*1

USB2.0 : front*1, rear*4

Hot-swap SATA bay*8

Gigabit LAN port * 1

RAID 5

482.6(L)*485.9(W)*88 (H) mm

Software Specification

Recording	<ul style="list-style-type: none">Recording Speed: Max. 64CH, 1920FPS/HD recordingRecording Mode: Continuous/motion/alarm recording, multiple continuous/motion/alarm recording schedulesRecording Buffer: Adjustable for pre-event recording and post-event recording, recycle HDD and keep video days
Dual Local Monitor	<ul style="list-style-type: none">Clone mode, two live view mode, live view + playback mode
Local live view	<ul style="list-style-type: none">Display Speed: Max. 64CH, 400FPS/HD real-time monitoringDisplay Mode: 1, 2X2, 3X3, 3X4(or 4X4), 6x6, 8X8, sequential and event video view modeDisplay Resolution: 1920X1080Display Control: video snapshot, optical PTZ/digital PTZ control and audio controlOSD information: camera name, date/time, record/event status
Local Playback	<ul style="list-style-type: none">Playback Speed: Max. 16CH playbackPlayback Mode: 1, 2X2, 3X3, 3X4(or 4X4) view modeSearch Mode: By timeline, motionPlayback Control: Play, pause, reverse play, previous frame/next frame, speed control(1, 2,4, 8, 16), video snapshot, digital zoom and audio controlExport: convert recording video to AVI, ASF or MKV format and export to USB storage
Remote Live View	<ul style="list-style-type: none">View Mode: 1, 2X2, 3X3, 3X4 (or4X4), 8X8 and sequential display from multi-site NVR servers simultaneouslyOSD information: camera name, date/time, record/event statusView Control: Full screen display, original video aspect ratio, video snapshot, optical PTZ/digital PTZ control and audio controlDevice Tree: Tree View listing and managementEvent Control: Event List, Digital Input status and digital output control
Remote Playback	<ul style="list-style-type: none">Playback Mode: Max. 4CH playbackPlayback Mode: 1, 2X2 view modeSearch Mode: By timeline



E-mail : service@multitek.com.tw
Web : www.multitek.com.tw