


MC-0804P


LED / 656 x 496 Pixel / Ø 4.8 mm

1/8" CCIQ II Color

MC-0804L



MC-0804P



unit : mm (±0.5)

Feature

- High Sensitivity!
- High Performance.
- 1/8" CCIQ II Color
- Ø 4.8 mm only
- 656 x 496 Pixel
- LED x 4

Specification

Model	MC-0804L	MC-0804LK	MC-0804P	MC-0804PK
Pixel size	2.8 um x 2.8um			
Effective Image Area	1.837 mm x 1.389 mm			
Video system	NTSC / PAL			
Number of effective pixels	656 x 496 (NTSC & PAL)			
Image sensor	1/8" CCIQ II Color Camera			
Resolution(TV Lines)	400 TV Lines			
S/N Ratio	41.6 dB			
Dynamic range	56.4 dB			
Sensor scan mode	progressive scan			
Minimum illumination	1LUX / F1.2			
Shutter Speed	30 fps.	15 fps.	30 fps.	15 fps.
Sensitivity	0.94V /Lux.sec			
Horizontal sync frequency	NTSC -15.734kHz , PAL - 15.625kHz			
Vertical sync frequency	NTSC - 60Hz , PAL - 50Hz			
Camera consumption	0.45			
Video output	1Vp-p , 75ohm composite			
Built - lens	1.85mm/ F2.8			
Storage temperature	-30 to 60 Degree C			
Working temperature	-10 to 45 Degree C			
Power source	DC 3.3~5V			
Power current	130 mA(max)			
Dimension (mm)	(D)5.5 mm(camera head)+ 70+16x4.5mm(main board)		(D)4.8 mm(camera head)+ 70+16x4.5mm(main board)	



MC-0804L



MC-0804P



Other information

MODEL	Max. Frame Rate	Water proof	LED Light
MC-0804L	30 fps.	water proof IP67	White LED x 4
MC-0804LK	15 fps.	water proof IP67	White LED x 4
MC-0804	30 fps.	water proof IP67	X
MC-0804K	15 fps.	water proof IP67	X
MC-0804P	30 fps.	X	X
MC-0804PK	15 fps.	X	X

note:

Other information

MC-1003

- 1/10" CCIQ II
- Lens : 2.5 mm Only !!

1/10" Color CCIQ II Camera
 Pixel : 400 x 400 (NTSC / PAL)
 3300mV/Lux
 Sensor board: (D)2.5 x 5 (mm)
 +
 Main board: 70 x 15(mm)

